













	Compact down. IP44 (steel)	2x10-DEL 26 W	20	Compact downlight, oporne do nadświetlenia IP44
	Compact down. (steel)	2x10-DEL 26 W	17	Compact downlight, oporne do nadświetlenia
	Morasun (steel)	1x16 W 54 V	14	Morasun, oporne nadświetlo IP65
	Compact down. IP44 (steel)	1x10-DEL 26 W	17	Compact downlight, oporne do nadświetlenia IP44
	Clean room lum. (steel)	4x16W 24 V	6	Clean room luminaires, oporne do nadświetlenia do szuflady MSF, IP54
	Sitelco laurre lum. M (steel)	2x16 W 54 V	20	Sitelco laurre luminaires M, oporne do nadświetlenia do szuflady MSF, IP54
	Sitelco laurre lum. XS (steel)	2x16 W 28 V	19	Sitelco laurre luminaires XS, oporne do nadświetlenia do szuflady MSF, IP54
	Sitelco laurre lum. M (steel)	3x16 W 24 V	20	Sitelco laurre luminaires M, oporne do nadświetlenia do szuflady MSF, IP45
	Sitelco laurre lum. M (steel)	4x16 W 24 V	20	Sitelco laurre luminaires M, oporne do nadświetlenia do szuflady MSF, IP45
	Sitelco laurre lum. M (steel)	2x16 W 24 V	20	Sitelco laurre luminaires M, oporne do nadświetlenia do szuflady MSF, IP45
	APPLY I (steel)	1x10-0 26 W	7	APPLY I - oporne lampa kieszon. IP65
	EMLEDPC	1x16 W 54 V	20	EMLEDPC - oporne nadświetlenie
	EMLEDPC	1x16 W 54 V	20	Oporno oświetlenia nadświetlenie
	SIAM LED	4x16 W 24 V	14	SIAM LED, oporne nadświetlenie
	Nadświetlenie (steel)	4x16 W 24 V	6	Oporno nadświetlenie, klasa IP65